

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

What is claimed is:

Sub  
A37

1. A device for driving an endless belt, comprising:  
belt driving means positioned at one end of the belt  
and comprising a first roller for moving said belt;

at least one rotary body arranged side by side in  
a direction of movement of the belt and pressed against  
said belt either directly or indirectly to be thereby  
rotated by said belt; and

a second roller adjoining said first roller and  
contacting the belt at a side where said rotary body is  
positioned;

wherein said first roller and said second roller each  
have allowable eccentricity reduced to a range that does  
not effect a variation of a speed of the belt.

2. The device as claimed in claim 1, wherein said  
belt driving means further comprises a motor.

3. The device as claimed in claim 2, wherein dynamic  
balance is set up on a rotary portion of said motor and  
said first roller integrally.

4. The device as claimed in claim 3, wherein said  
first roller and a shaft of said first roller are molded  
integrally with each other.

5. The device as claimed in claim 4, wherein dynamic  
balance is set up on a rotary portion of said motor and  
said first roller integrally.

09985741-110501

Sub  
A3  
cont

6. The device as claimed in claim 2, further comprising an eccentricity adjusting mechanism assigned to at least one of said first roller and said second roller.

7. The device as claimed in claim 6, wherein dynamic balance is set up on a rotary portion of said motor and said first roller integrally.

8. The device as claimed in claim 7, wherein said first roller and a shaft of said first roller are molded integrally with each other.

9. The device as claimed in claim 8, wherein dynamic balance is set up on a rotary portion of said motor and said first roller integrally.

10. A device for driving an endless belt, comprising:  
belt driving means positioned at one end of the belt and comprising a drive roller for moving said belt;

at least one rotary body arranged side by side in a direction of movement of the belt and pressed against said belt either directly or indirectly to be thereby rotated by said belt; and

a stationary guide body adjoining said drive roller and contacting the belt at a side where said rotary body is positioned;

wherein said drive roller has allowable eccentricity reduced to a range that does not effect a variation of a speed of the belt.

0995741-11061  
FOUOT 429860

Sub  
A3  
cont

11. The device as claimed in claim 10, wherein said belt driving means further comprises a motor.

12. The device as claimed in claim 11, wherein dynamic balance is set up on a rotary portion of said motor and said drive roller integrally.

13. The device as claimed in claim 11, wherein said drive roller and a shaft of said drive roller are molded integrally with each other.

14. The device as claimed in claim 13, wherein dynamic balance is set up on a rotary portion of said motor and said drive roller integrally.

15. A device for driving an endless belt, comprising:  
belt driving means positioned at one end of the belt for moving said belt;

a driven roller positioned at the other end of the belt remote from said belt driving means;

a plurality of rotary bodies arranged side by side in a direction of movement of the belt and pressed against said belt either directly or indirectly to be thereby rotated by said belt; and

at least one tension roller positioned between said plurality of rotary bodies, between said belt driving means and said plurality of rotary bodies or between said driven roller and said plurality of rotary bodies.

16. A device for driving an endless belt, comprising:

09985741-110501

Sub  
A3  
cont 7

belt driving means positioned at one end of the belt for moving said belt and comprising a drive roller;

at least one rotary body arranged side by side in a direction of movement of the belt and pressed against said belt either directly or indirectly to be thereby rotated by said belt; and

tension rollers positioned at both sides of a position where the belt contacts said rotary body.

17. An image forming apparatus comprising:

belt driving means positioned at one end of the endless belt, which is one of at least an intermediate image transfer belt and a sheet conveying belt, and comprising a drive roller for moving said belt; and

at least one photoconductive drum arranged side by side in a direction of movement of the belt and pressed against said belt either directly or indirectly to be thereby rotated by said belt;

wherein at least one of said drive roller and said photoconductive drum is directly driven by an outer rotor coreless motor.

18. The apparatus as claimed in claim 17, wherein torque ripples generated by said outer rotor coreless motor are set at a spatial frequency close to a maximum value in an allowable, torque ripple spatial frequency range at a low frequency side, which does not effect image

09985741 110601

Sub  
A3  
cont

quality.

19. The apparatus as claimed in claim 18, wherein said outer rotor coreless motor comprises an outer rotor functioning as said drive roller at the same time.

20. The apparatus as claimed in claim 19, wherein the outer rotor comprises an encoder disk on which at least one of timing marks for sensing a signal for rotation control and a mark for sensing a signal that switches a phase of a current to be fed to each of different coil phases.

21. The apparatus as claimed in claim 20, wherein said mark functions as a mark for sensing a start signal output for each rotation at the same time.

22. The apparatus as claimed in claim 18, wherein said outer rotor coreless motor comprises an outer rotor that is formed integrally with said drive roller.

23. The apparatus as claimed in claim 22, wherein the outer rotor comprises an encoder disk on which at least one of timing marks for sensing a signal for rotation control and a mark for sensing a signal that switches a phase of a current to be fed to each of different coil phases.

24. The apparatus as claimed in claim 23, wherein said mark functions as a mark for sensing a start signal output for each rotation at the same time.

09985744 "110601

Sub  
A3  
cont

25. The apparatus as claimed in claim 18, wherein said outer rotor coreless motor is driven such that timings for feeding currents to coils of different phases substantially do not overlap each other when a flux density of a bore magnetic field is substantially constant.

26. The apparatus as claimed in claim 25, wherein the outer rotor comprises an encoder disk on which at least one of timing marks for sensing a signal for rotation control and a mark for sensing a signal that switches a phase of a current to be fed to each of different coil phases.

27. The apparatus as claimed in claim 26, wherein said mark functions as a mark for sensing a start signal output for each rotation at the same time.

28. The apparatus as claimed in claim 18, wherein the outer rotor comprises an encoder disk on which at least one of timing marks for sensing a signal for rotation control and a mark for sensing a signal that switches a phase of a current to be fed to each of different coil phases.

29. The apparatus as claimed in claim 28, wherein said mark functions as a mark for sensing a start signal output for each rotation at the same time.

30. The apparatus as claimed in claim 17, wherein said outer rotor coreless motor comprises an outer rotor

0995741-110501

Sub  
A3  
cont

functioning as said drive roller at the same time.

31. The apparatus as claimed in claim 30, wherein the outer rotor comprises an encoder disk on which at least one of timing marks for sensing a signal for rotation control and a mark for sensing a signal that switches a phase of a current to be fed to each of different coil phases.

32. The apparatus as claimed in claim 31, wherein said mark functions as a mark for sensing a start signal output for each rotation at the same time.

33. The apparatus as claimed in claim 17, wherein said outer rotor coreless motor comprises an outer rotor that is formed integrally with said drive roller.

34. The apparatus as claimed in claim 33, wherein said mark functions as a mark for sensing a start signal output for each rotation at the same time.

35. The apparatus as claimed in claim 34, wherein said outer rotor coreless motor comprises an outer rotor that is formed integrally with said drive roller.

36. The apparatus as claimed in claim 17, wherein said outer rotor coreless motor is driven such that timings for feeding currents to coils of different phases substantially do not overlap each other when a flux density of a bore magnetic field is substantially constant.

37. The apparatus as claimed in claim 36, wherein

099854-11050  
T0907T-14258660



Sub  
A3  
Cont

said mark functions as a mark for sensing a start signal output for each rotation at the same time.

38. The apparatus as claimed in claim 37, wherein said outer rotor coreless motor comprises an outer rotor that is formed integrally with said drive roller.

39. The apparatus as claimed in claim 17, wherein said mark functions as a mark for sensing a start signal output for each rotation at the same time.

40. The apparatus as claimed in claim 39, wherein said outer rotor coreless motor comprises an outer rotor that is formed integrally with said drive roller.

Add  
A3

099574-11050  
T090T-14258660